Material Safety Data Sheet

Butyl Acrylate Monomer (RXSOL-19-1581-210)

1. Product and Company Identifaction

Product Name	RXSOL-19-1581-210
Product Type	Butyl Acrylate Monomer

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone	+91 22 65113333 / 5555 / 9999 / 27815540
Fax	+91 22 2781 1318 :::AOH :0091 9821214367
Email	mail@rxmarine.com
Website	www.rxmarine.com

2. Composition / informationon ingredients

Chemical Name	CAS Number	EC Number	Index number
n-butyl acrylate	141-32-2	205-480-7	607-062-00-3

3. Hazards Identification

Hazard description:
Information concerning particular hazards for human and environment:
R 10 Flammable.
R 36/37/38 Irritating to eyes, respiratory system and skin.
R 43 May cause sensitisation by skin contact.

4. First Aid Measures

After inhalation	Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.
After skin contact	Immediately wash with water and soap and rinse thoroughly.
After eye contact	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing	If symptoms persist consult doctor.

5. Fire-fighting Measures

Suitable extinguishing agents:
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
For safety reasons unsuitable extinguishing agents: Water with full jet
Protective equipment: No special measures required.

6. Accidental Release Measures

Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
Measures for cleaning/collecting: Dilute with plenty of water. Ensure adequate ventilation.

7. Handling and Storage

Handling:
Information for safe handling: No special requirement
Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: Not required.
Further information about storage conditions: Keep container tightly sealed.

8. Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

141-32-2 n-butyl acrylate

REL (USA)	55 mg/m³, 10 ppm 11 mg/m³, 2 ppm
TLV (USA)	SEN Short-term value: 53 mg/m³, 10 ppm
IOELV (EU)	Long-term value: 11 mg/m³, 2 ppm
WEL (Great Britain)	Short-term value: 26 mg/m³, 5 ppm Long-term value: 5 mg/m³, 1 ppm

Additional information: The lists valid during the making were used as basis.
Personal protective equipment:
General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Material of gloves: The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material:
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
Eye protection: Tightly sealed goggles

9. Physical and chemical properties

General Information

Form	Fluid
Colour	Colourless
Odour	Fruit-like
Change in condition	

Melting point/Melting range	-64.6°C
Boiling point/Boiling range	145°C
Flash point	37°C
Ignition temperature	275°C
Danger of explosion	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower	1.2 Vol %
Upper	8 Vol %
Vapour pressure at 20°C	5.3 hPa
Density at 20°C	0.8898 g/cm³
Solubility in / Miscibility with water at 20°C	1.4 g/l

10. Stability and reactivity

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
Dangerous reactions No dangerous reactions known.
Dangerous decomposition products: No dangerous decomposition products known.

11. Toxicological information

Acute toxicity:

LD/LC50 values relevant for classification:

Oral	LD50	900 mg/kg (rat)
Dermal	LC50	2000 mg/kg (rabbit)

Primary irritant effect:

on the skin	Irritant to skin and mucous membranes.
on the eye	Irritating effect.
Sensitization	Sensitization possible through skin contact.

12. Ecological information

General notes: Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13. Disposal considerations

Product:
Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

14. Transport information

Land transport ADR/RID (cross-border)

ADR/RID class	3 Flammable liquids.
Danger code (Kemler)	39

	UN-Number	2348
	Packaging group	III
	Hazard label	3
	Description of goods	2348 BUTYL ACRYLATES, STABILIZED
Maritime transport IMDG		
	IMDG Class	3
	UN Number	2348
	Label	3
	Packaging group	III
	EMS Number	F-E,S-D
	Marine pollutant	No
	Proper shipping name	BUTYL ACRYLATES, STABILIZED
Air transport ICAO-TI and IATA-DGR		
	ICAO/IATA Class	3
	UN/ID Number	2348
	Label	3
	Packaging group	III
	Proper shipping name	BUTYL ACRYLATES, STABILIZED

15. Regulatory information

Labelling according to EU guidelines:
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
Risk phrases:
10 Flammable.
36/37/38 Irritating to eyes, respiratory system and skin.
43 May cause sensitisation by skin contact.
Safety phrases:
2 Keep out of the reach of children.
9 Keep container in a well-ventilated place.

16. Other information

This information is based on our present knowledge.However, this shall not constitute a guarantee for anys pecific product features and shall not establish a legally valid contractual relationship.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.