Material Safety Data Sheet

Floor Polish (Metlic) (RXSOL-13-1643-005)

1. Product and Company Identifaction

Product Name	RXSOL-13-1643-005
Product Type	**Floor Polish (Metalic)**

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone	+91 22 65113333 / 5555 / 9999
Fax	+91 22 2781 1318 :::AOH :0091 9821214367
Email	mail@rxmarine.com

2. Composition / informationon ingredients

INGREDIENTS	Conc % W/W	CAS no	EXPOSITION CL50	LETHAL DOSE INGESTION DL50
Acrylic polymer ULTRA K	30 - 60	T.Secret	N/D	N/D
2-(2-Methoxyethoxy) ethanol	1 - 5	111-77-3	N/D	N/D

3. Hazards Identification

N/A

4. First Aid Measures

Contact with Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Occasionally lifting upper and lower lids. Get medical attention at once.
Contact with skin	It should be rinsed off with water.
Ingestion	If this product is swallowed, do not induce vomiting. If victim is conscious give plenty of water to drink. Get medical attention at once. (ANTIPOISON CENTER: 1-800-463-5060)
Inhalation	Move exposed person to fresh air. If irritation persists. Get medical attention promptly.

5. Fire-fighting Measures

Flammable	No
Condition	Nothing
Extinction	Chemical foam, carbon dioxide,
Flash Point (open cup)	water Superior at 95° C
Auto-inflammation temperature	N/D
Dangerous product made by combustion	Carbon oxide

6. Accidental Release Measures

Eyes Protection	Protectives Googles.
Respiratory Protection	You don't need a safety mask with normal using.
Skin Protection	Protectives cloths, Boots, Googles.
Technical installation	Put good ventilation for close chamber for eliminate a vapour could be concentrated.
Measures if a leaks and spills	Take off the leaks and put in a identify drums Rinse the floor with water
Elimination	Conform with federal and provincial laws Put in a closed material. Protect against the freeze

7. Handling and Storage

N/A

8. Exposure controls and personal protection

N/A

9. Physical and chemical properties

Physical State	White Liquid
boiling Point	> 100°C
Odor	Light Acrylic odor
pH	8.5± 0.5
Freezing Point	0°C
% Volatile	N/D
Density (20°C)	1.024 g/cc
Vapor Pressure	N/D
Water solubility	yes
Vapor Density	N/D

10. Stability and reactivity

Chemical stability	Stable
Incompatibility with other products	Strong reductor, strong oxidant and acid product.
Conditions	N/D
Polymerisation	None
Decomposition product	Carbon oxide

11. Toxicological information

Exposition limit	N/D
Absorption way	Inhalation ( ) Eyes (X) Skin ( ) Ingestion (X)
Chronics exposure with the product	N/D
Inhalation	No Object
Eyes	Irritation.
Skin	Should be irritating if the product is apply directly on skin
Ingestion	Irritation, nausea
Cancerogenicity	None
Synergics products	None

12. Ecological information

N/A

13. Disposal considerations

N/A

14. Transport information

N/A

15. Regulatory information

N/A

16. Other information

N/A