Material Safety Data Sheet

Vinyl Polish (Thermoplastic Floor Finish) (RXSOL-18-1049-005)

1. Product and Company Identifaction

Product Name	RXSOL-18-1049-005
Product Type	Vinyl Polish (Thermoplastic Floor Finish)

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone	+91 22 65113333 / 5555 / 9999
Fax	+91 22 2781 1318 :::AOH :0091 9821214367
Email	mail@rxmarine.com

2. Composition / informationon ingredients

HAZARDOUS INGREDIENTS

INGREDIENTS	Conc % W/W	CAS no	EXPOSITION CL50	LETHAL DOSE INGESTION DL50
Acrylic polymer ULTRA M	30 - 60	V.Secret	N/D	N/D
2-(2-Methoxyethoxy) ethanol	1 - 5	111-77-3	N/D	N/D

3. Hazards Identification

N/A

4. First Aid Measures

Contact with Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Occasionally lifting upper and lower lids. Get medical attention at once.
Contact with skin	It should be rinsed off with water.
Ingestion	If this product is swallowed, do not induce vomiting. If victim is conscious give plenty of water to drink. Get medical attention at once. (ANTIPOISON CENTER: 1-800-463-5060)
Inhalation	Move exposed person to fresh air. If irritation persists. Get medical attention promptly.

5. Fire-fighting Measures

Flammable	No
Condition	Nothing
Extinction	Chemical foam, carbon dioxide,
Flash Point (open cup)	water Superior at 95° C
Auto-inflammation temperature	N/D
Dangerous product made by combustion	Carbon oxide

6. Accidental Release Measures

Eyes Protection	Protectives Googles.
Respiratory Protection	You don't need a safety mask with normal using.
Skin Protection	Protectives cloths, Boots, Googles.
Technical installation	No caution are necessary
Measures if a leaks and spills	Take off the leaks and put in a identify container Rinse the floor with water.
Elimination	Conform with federal and provincial laws Put in a closed material. Protect against the freeze

7. Handling and Storage

N/A

8. Exposure controls and personal protection

N/A

9. Physical and chemical properties

Physical State	White Liquid
boiling Point	> 100°C
Odor	Light Acrylic odor
pH	8.5± 0.5
Freezing Point	0°C
% Volatile	N/D
Density (20°C)	1.034 g/cc
Vapor Pressure	N/D
Water solubility	yes
Vapor Density	N/D

10. Stability and reactivity

Chemical stability	Stable

Incompatibility with other products	Strong reductor, strong oxidant and acid product.
Conditions	N/D
Polymerisation	None
Decomposition product	Carbon oxide

11. Toxicological information

Exposition limit	N/D
Absorption way	Inhalation ( ) Eyes (X) Skin ( ) Ingestion (X)
Chronics exposure with the product	N/D
Inhalation	No Object
Eyes	Can be irriting eyes and can be paste eyelid
Skin	Can be irritating skin and paste on the skin
Ingestion	Dangerous
Cancerogenicity	None
Synergics products	None

12. Ecological information

N/A

13. Disposal considerations

N/A

14. Transport information

N/A

15. Regulatory information

N/A

16. Other information

N/A

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.