Material Safety Data Sheet

RESPIRATORY PROTECTION FULL MASKS (RXSOL-64-2628-001)

1. Product and Company Identifaction

Product Name **RESPIRATORY PROTECTION FULL MASKS**

Product Type **RXSOL-64-2628-001**

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone	+91 22 65113333/ 5555 / 9999 / 27611360 / 27815540
Fax	+91 22 2781 1318 :::AOH :0091 9322594669
Email	mail@rxmarine.com

2. Composition / informationon ingredients

Ingredient	CAS #	Weight Percent
Aliphatic Hydrocarbon	64742-47-8	45-50
Petroleum Base Oil	64742-58-1 64742-53-6 64742-56-9 64742-65-0	25
LVP Aliphatic Hydrocarbon	64742-47-8	12-18
Carbon Dioxide	124-38-9	2-3
Non-Hazardous Ingredients	Mixture	10

3. Hazards Identification

Emergency Overview:	DANGER! Flammable aerosol. Contents under pressure. Harmful or fatal if swallowed. If swallowed, may be aspirated and cause lung damage. May cause eye irritation. Avoid eye contact. Use with adequate ventilation. Keep away from heat, sparks and all other sources of ignition.
Symptoms of Overexposure:	
Inhalation:	High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

Skin Contact:	Prolonged and/or repeated contact may produce mild irritation and defatting with possible dermatitis.
Eye Contact:	Contact may be irritating to eyes. May cause redness and tearing.
Ingestion:	This product has low oral toxicity. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.
Chronic Effects:	None expected.
Medical Conditions Aggravated by Exposure:	Preexisting eye, skin and respiratory conditions may be aggravated by exposure.
Suspected Cancer Agent:	Yes No X

4. First Aid Measures

Ingestion (Swallowed):	Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.
Eye Contact:	Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists.
Skin Contact:	Wash with soap and water. If irritation develops and persists, get medical attention.
Inhalation (Breathing):	If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

5. Fire-fighting Measures

Extinguishing Media:	Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.
Special Fire Fighting Procedures:	Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting containers.
Unusual Fire and Explosion Hazards:	Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back.

6. Accidental Release Measures

Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area. Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

7. Handling and Storage

Handling	Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty.
Storage	Store in a cool, well-ventilated area, away from incompatible materials. Do not store above 120?F or in direct sunlight. U.F.C (NFPA 30B) Level 3 Aerosol.

8. Exposure controls and personal protection

Chemical	Occupational Exposure Limits
Aliphatic Hydrocarbon	1200 mg/m3 TWA (manufacturer recommended)
Petroleum Base Oil	5 mg/m3 TWA, 10 mg/m3 STEL ACGIH TLV 5 mg/m3 TWA OSHA PEL
LVP Aliphatic Hydrocarbon	1200 mg/m3 TWA (manufacturer recommended)
Carbon Dioxide	5000 ppm TWA (OSHA/ACGIH), 30,000 ppm STEL (ACGIH)
Non-Hazardous Ingredients	None Established

The Following Controls are Recommended for Normal Consumer Use of this Product	
Engineering Controls:	Use in a well-ventilated area.

Personal Protection:	
Eye Protection:	Avoid eye contact. Always spray away from your face.
Skin Protection:	Avoid prolonged skin contact. Chemical resistant gloves recommended for operations where skin contact is likely.
Respiratory Protection:	None needed for normal use with adequate ventilation.
For Bulk Processing or Workplace Use the Following Controls are Recommended	
Engineering Controls:	Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.
Personal Protection:	
Eye Protection:	Safety goggles recommended where eye contact is possible.
Skin Protection:	Wear chemical resistant gloves.
Respiratory Protection:	None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.
Work/Hygiene Practices:	Wash with soap and water after handling.

9. Physical and chemical properties

Boiling Point:	361 - 369?F (183 - 187°C)
Solubility in Water:	Insoluble
Vapor Pressure:	95-115 PSI @ 70?F
Percent Volatile:	70-75%
Coefficient of Water/Oil Distribution:	Not Determined
Flash Point:	122?F (49°C) Tag Open Cup (concentrate)
Pour Point:	-63?C (-81.4?F) ASTM D-97
Specific Gravity:	0.8 – 0.82 @ 60?F
pH:	Not Applicable

Vapor Density:	Greater than 1
VOC:	412 grams/liter (49.5%)
Appearance/Odor	Light amber liquid/mild odor
Flammable Limits: (Solvent Portion)	LEL: 0.6% UEL: 8.0%
Kinematic Viscosity:	2.79-2.96cSt @ 100?F

10. Stability and reactivity

Stability:	Stable
Hazardous Polymerization:	Will not occur.
Conditions to Avoid:	Avoid heat, sparks, flames and other sources of ignition. Do not puncture or incinerate containers.
Incompatibilities:	Strong oxidizing agents.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide.

11. Toxicological information

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.
None of the components of this product is listed as a carcinogen or suspected carcinogen or is considered a reproductive hazard.

12. Ecological information

No data is currently available.

13. Disposal considerations

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations.

14. Transport information

DOT Surface Shipping Description: Consumer Commodity, ORM-D
After 1/1/2014 UN1950, Aerosols, 2.1 Ltd. Qty (Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)
IMDG Shipping Description: UN1950, Aerosols, 2.1, LTD QTY
ICAO Shipping Description: UN1950, Aerosols, flammable, 2.1 NOTE: WD-40 does not test aerosol cans to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our aerosol products be transported by air.

15. Regulatory information

U.S. Federal Regulations:

CERCLA 103 Reportable Quantity:	This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312:	Acute Health, Fire Hazard, Sudden Release of Pressure
Section 313 Toxic Chemicals:	This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None Section 302 Extremely Hazardous Substances (TPQ): None
EPA Toxic Substances Control Act (TSCA) Status:	All of the components of this product are listed on the TSCA inventory.
California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):	This product does not contain chemicals regulated under California Proposition 65.
VOC Regulations:	This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.
Canadian Environmental Protection Act:	One of the components is listed on the NDSL. All of the other ingredients are listed on the Canadian Domestic Substances List or exempt from notification.
Canadian WHMIS Classification:	Class B-5 (Flammable Aerosol)

This MSDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

16. Other information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Rx Marine International be liable for any claims, losses, or

damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages.