Material Safety Data Sheet

PARAFFIN OIL (RXSOL-60-6020-002)

1. Product and Company Identifaction

Product Name	**PARAFFIN OIL**
Product Type	**RXSOL-60-6020-002**

Company Details:
RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Gandhidham, Chennai, Visakhapatnam, Kolkata, Fujairah, Muscat Oman

Phone	+91 22 27815540 / 41 / 42
Fax	+91 22 2781 1318 :::AOH :0091 9322594669
Email	mail@rxmarine.com

2. Composition / informationon ingredients

Name	CAS #	% by Weight
Wax Paraffin	8002-74-2 or 64742-43-4	100

?Toxicological Data on Ingredients: Not applicable.

3. Hazards Identification

Potential Acute Health Effects:
Slightly hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation.

Potential Chronic Health Effects:
CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.

4. First Aid Measures

Eye Contact:	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin Contact:	Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops.
Serious Skin Contact:	Not available.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Serious Inhalation:	Not available.
Ingestion:	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.
Serious Ingestion:	Not available.

5. Fire-fighting Measures

Flammability of the Product:	May be combustible at high temperature.
Auto-Ignition Temperature:	245°C (473°F) - 340 C
Flash Points:	CLOSED CUP: 199°C (390.2°F). OPEN CUP: 235°C (455°F).
Flammable Limits:	Not available.
Products of Combustion:	Not available.
Fire Hazards in Presence of Various Substances:	Slightly flammable to flammable in presence of heat. Non-flammable in presence of shocks.
Explosion Hazards in Presence of Various Substances:	Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.
Fire Fighting Media and Instructions:	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.
Special Remarks on Fire Hazards:	Not available.
Special Remarks on Explosion Hazards:	Not available.

6. Accidental Release Measures

Small Spill:	Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.
Large Spill:	Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

7. Handling and Storage

Precautions:
Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area.

8. Exposure controls and personal protection

Engineering Controls:
Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection:Safety glasses. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:
Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:
Parrafin Wax (Fume) TWA: 2 STEL: 6 (mg/m3) [Canada] TWA: 2 (mg/m3) from OSHA (PEL) [United States] TWA: 2 (mg/ m3) from ACGIH (TLV) [United States] TWA: 2 (mg/m3) from NIOSH [United States] TWA: 2 STEL: 6 [United Kingdom (UK)]Consult local authorities for acceptable exposure limits.

9. Physical and chemical properties

Physical state and appearance:	Solid.
Odor:	Odorless.
Taste:	Not available.
Molecular Weight:	Not applicable.

Color:	White.
pH (1% soln/water):	Not applicable.
Boiling Point:	Not available.
Melting Point:	47°C (116.6°F) - 65 C
Critical Temperature:	Not available.
Specific Gravity:	0.9 @ 20 deg. C 0.92 @ 25 deg. C (Water = 1)
Vapor Pressure:	Not applicable.
Vapor Density:	Not available.
Volatility:	Not available.
Odor Threshold:	Not available.
Water/Oil Dist. Coeff.:	Not available.
Ionicity (in Water):	Not available.
Dispersion Properties:	Not available.
Solubility:	Insoluble in cold water, hot water.

10. Stability and reactivity

Stability:	The product is stable.
Instability Temperature:	Not available.
Conditions of Instability:	Excess heat
Incompatibility with various substances:	Reactive with oxidizing agents.
Corrosivity:	Non-corrosive in presence of glass.
Special Remarks on Reactivity:	Not available.
Special Remarks on Corrosivity:	Not available.
Polymerization:	Will not occur.

11. Toxicological information

Routes of Entry:	Eye contact. Inhalation. Ingestion.
Toxicity to Animals:	LD50: Not available. LC50: Not available.
Chronic Effects on Humans:	Not available.
Other Toxic Effects on Humans:	Slightly hazardous in case of skin contact (irritant), of ingestion, of inhalation.
Special Remarks on Toxicity to Animals:	Not available.
Special Remarks on Chronic Effects on Humans:	Not available.
Special Remarks on other Toxic Effects on Humans:	Acute Potential Health Effects: Skin: Solid material is not expected to be an irritant, but it may cause mild skin irritation. Eyes: Solid materials is not expected to be an irritant, but it may cause mild eye irritation. Vapors from molten wax may cause eye irritation. Inhalation: Low hazard. Paraffin wax fumes may be irritating to the eyes nose and throat. and may also produce nausea. 'However, vapors emitted from molten wax are expected to have a low degree of irritation by inhalation. Ingestion: Ingested paraffin wax is not absorbed, and is considered nontoxic. Ingestion of large amounts may have a mild laxative effect and cause diarrhea. Chronic Potential Health Effects: Skin: Poor personal hygiene can lead to wax plugging of skin follicles and producing so-called "Wax Boils".

12. Ecological information

Ecotoxicity:	Not available.
BOD5 and COD:	Not available.

Products of Biodegradation:	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.
Toxicity of the Products of Biodegradation:	Not available.
Special Remarks on the Products of Biodegradation:	Not available.

13. Disposal considerations

Waste Disposal: Waste must be disposed of in accordance with federal, state and local environmental control regulations.

14. Transport information

DOT Classification:	Not a DOT controlled material (United States).
Identification:	Not applicable.
Special Provisions for Transport:	Not applicable.

15. Regulatory information

Federal and State Regulations:
Illinois toxic substances disclosure to employee act: Wax (Paraffin) Fume Rhode Island RTK hazardous substances: Wax (Paraffin) Fume Pennsylvania RTK: Wax (Paraffin) Minnesota: Wax (Paraffin) Fume Massachusetts RTK: Wax (Paraffin) Fume TSCA 8(b) inventory: Wax (Paraffin)

Other Regulations: EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:
WHMIS (Canada): Not controlled under WHMIS (Canada).

DSCL (EEC):This product is not classified according to the EU regulations. Not applicable.

HMIS (U.S.A.):

Health Hazard:	1
Fire Hazard:	1
Reactivity:	
Personal Protection:	E

National Fire Protection Association (U.S.A.):

Health:	0
Flammability:	1
Reactivity:	0
Specific hazard:	

Protective Equipment: Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Safety glasses.

16. Other information

Text of R and S phrase codes used in this safety data sheet:- R34: Causes burns; R36: Irritating to eyes; R37:Irritating to respiratory system; R41: Risk of serious damage to eyes. The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications usage in such may cause risks not mentioned in this sheet. Do not use for other application(s) without seeking advice from manufacturer.