Material Safety Data Sheet

Ultrapac Trafficlean (RXSOL-41-8402-025)

1. Product and Company Identifaction

Product Name	**ULTRAPAC TRAFFICLEAN**
Product Type	**RXSOL-41-8402-025**

Company Details:
RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone	+91 22 65113333/ 5555 / 9999 / 27611360 / 27815540
Fax	+91 22 2781 1318:::AOH :0091 9322594669
Email	mail@rxmarine.com

2. Composition / informationon ingredients

Ingredients:

CAS #	Percent	Chemical Name
111762	24%	Ethylene glycol monobutyl ether

OSHA Regulatory Status:
This MSDS Contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.

3. Hazards Identification

Route of Entry: Eyes; Skin; Inhalation; Ingestion;
Target Organs: Eyes; Skin;
Inhalation: Minimal respiratory tract irritation may occur with exposure to a large amount of material
Skin Contact: May cause irritation.
Eye Contact: May cause irritation.
Ingestion: Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause temporary injury.

4. First Aid Measures

Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact: Wash with soap and water. If irritation persists consult medical personnel.
Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.

Ingestion: If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

5. Fire-fighting Measures

Flash Point: 200°F
Flash Point Method: Closed Cup
Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

6. Accidental Release Measures

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Pick up excess with inert absorbent material and place into separate waste container. Ventilate area and wash spill site after material pickup is complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

7. Handling and Storage

Handling Precautions: Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid spillage on the floor (slippage). Keep away from sources of ignition; wash thoroughly after handling.
Storage Requirements: Store out of reach of children; keep container closed; store in a cool well-ventilated place.

8. Exposure controls and personal protection

Engineering Controls: Normal room ventilation is satisfactory for limited use.
Personal Protective Equip:HMIS PP, B Safety glasses, Gloves
Ethylene glycol monobutyl ether 111-76-2 OSHA PEL 50 ppm - 240 mg/m3

9. Physical and chemical properties

Appearance	Opaque Caramel
Physical State	Liquid
pH	9.5 - 10.2 as is
Odor	Mint
Solubility	Soluble
Spec Grav./Density	9.44 lb/gallon

10. Stability and reactivity

Stability:Product is stable under normal conditions.
Conditions to Avoid:None known
Materials to Avoid:None known
Hazardous Decomposition:Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.
Hazardous Polymerization:Will not occur

11. Toxicological information

Toxicity Data:
Ethylene glycol butyl ether 111-76-2
Oral (LD 50): 917 mg/kg - Rat
Inhalation (LC 50): 2900 mg/m3/7H - Rat
Skin irritation: Mild
Eye irritation: Mild
Sensitation: Not considered an occupational sensitizer

12. Ecological information

On the basis of available information, this material is not expected to produce any significant environmental effects when recommended use instructions are followed.

13. Disposal considerations

Dispose of in accordance with local regulations.

14. Transport information

DOT Class: Not regulated #
Ship in accordance with 49 CFR parts 100-185. Non-hazardous for air, sea and road freight.

15. Regulatory information

COMPONENT / (CAS/PERCENT) /CODES
*Ethylene glycol monobutyl ether (111762 24%) HAP, MASS, OSHAWAC, PA, TXAIR, WHMIS
REGULATORY KEY DESCRIPTIONS
All components are listed on TSCA
HAP = Hazardous Air Pollutants
MASS = MA Masssachusetts hazardous Substances List
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right - to - Know List of Hazardous substance
TXAIR = TX Air Contaminants with Health Effects Screening Level
WHMIS = Workplace Hazardous Material Information System

16. Other information

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.