Material Safety Data Sheet

HEAVY DUTY DEODORIZING ADDITIVE (RXSOL-41-8509-025)

1. Product and Company Identifaction

Product Name	HEAVY DUTY DEODORIZING ADDITIVE
Product Type	RXSOL-41-8509-025

Company Details:
RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone	+91 22 65113333/ 5555 / 9999 / 27611360 / 27815540
Fax	+91 22 2781 1318 :::AOH :0091 9322594669
Email	mail@rxmarine.com

2. Composition / informationon ingredients

PRINCIPLE HAZARDOUS INGREDIENTS : TLV %

Isopropyl Alcohol 400 PPM

Blended odor counteractants

3. Hazards Identification

Route(s) of entry

Health Hazards:

Eyes? Yes Skin? Yes Inhalation? Yes Ingestion? Yes

Eyes – May cause irritation

Skin – May be mild nasal and respiratory system irritant.

Inhalation – Over exposure to humans is suggested as a cause of kidney damage

Ingestion – Over exposure to humans is suggested as a cause of kidney damage

Carcinoginicity:NTP? N/A OSHA? N/A IARC Monograph? N/A

4. First Aid Measures

Eyes: Flush with water.If irritation persists,See a physician.

Skin: Wash skin.If irritation persists,See a physician.

Inhalation : move victim from exposure.If irritation persists,See a physicain

Ingestion: If irritation persists,See a physician.

5. Fire-fighting Measures

Flash Point: >70º F

ExtinguishingMedia: Dry chemical CO2, alcohol – type foam. Water may be ineffective.

Special Fire Fighting Procedures: In case of bulk spill, use water spray to cool fire exposed surfaces and to protect personnel.

Unusual Fire and Explosion Hazards: Respiratory protection required for fire personnel. Stay upwind.

Stability: Stable

Chemical Incompatibility: Avoid strong oxidizers. Do not store or heat above 120º F in aluminum containers

Hazardous Decomposition or Byproducts: Carbon monoxide and unidentified organic compounds may form during combustion

Hazardous Polymerization: Will not occur

Conditions to Avoid: Excessive heat

6. Accidental Release Measures

FLAMMABLE LIQUID. Extinguish ignition sources. Handling equipment must be grounded. Absorb liquid and place spent absorbent in non-leaking containers. Ignitable hazardous waste #D001. All disposal must be in accordance with all federal, state and local regulations.

7. Handling and Storage

Respiratory Protection : Use NOISH approved respirator to prevent over exposure.

Protective Clothing :Rubber gloves

Eye Protection : Protective goggles

Ventilation : Ni smoking,use with good ventilation

Storage : Store in cool area

8. Exposure controls and personal protection

9. Physical and chemical properties

Boiling Point (oF)	179.6º f
Vapor Pressure (mmHg.)	62
Vapor Density (AIR=1)	N/A
Solubility in Water	Moderate
Specific Gravity(H2O=1)	(@60º F) .894
Percent Volatile by Volume	N/A
PH	N/A
Appearance & Odor	Light yellow color, strong sweetish aroma

10. Stability and reactivity

11. Toxicological information

12. Ecological information

13. Disposal considerations

14. Transport information

15. Regulatory information

16. Other information

While this information and recommendations set forth herein are believed to be accurate and reliable, it is provided without warranty regarding its accuracy. BRIDGEPOINT SYSTEMS MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON. Users must determine safe conditions for use and assume liability for any loss, injury, damage or expense resulting from use of this product.

N/A = Not applicable N/D = Not determined N/E = Not established