Material Safety Data Sheet

Carpet Stain Remover (RXSOL-15-8971-005)

1. Product and Company Identifaction

Product Name	Carpet Stain Remover
Product Type	**RXSOL-41-8971-005**

Company Details:
RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Kolkata, Chennai, Visakhapatnam, Fujairah.

Phone	+91 22 27815540 / 27815541 / 42
Fax	+91 22 2781 1318 :::AOH :0091 9322594669
Email	mail@rxmarine.com

2. Composition / informationon ingredients

CHEMICAL NAME	CAS NO.	SARA III LIST	OSHA PEL	ACGIH TLV
Ammonium Hydroxide	1336-21-6			
Hydrogen Peroxide	7722-84			

Other non-hazardous ingredients constitute less than 1%, This product does not contain any toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and
Community Right-To-Know Act of 1986 and of 40 CFR 372.

3. Hazards Identification

Health 1	Flammability 0	Reactivity 0	Personal Protection

HAZARD INDEX: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe

4. First Aid Measures

Effects of Overexposure:
Skin: Prolonged or repeated contact can cause dryness and irritation. Eyes: Liquid or vapor contact can cause irritation. Inhalation:
Although unlikely to occur extremely high concentrations of vapor, mist or liquid contact can irritate respiratory tract. Ingestion: May cause naseau, vomiting, upset stomach, diarrhea. Chronic Effects: None anticipated.

First Aid Procedures:
Skin:(liquid only) Flush with water. Seek medical attention if irritation persists. Eyes:(liquid only) Flush with water for 15 minutes. Seek medical attention. Inhalation: Remove to fresh air. Call physician immediately. Ingestion: DO NOT INDUCE VOMITING. Rinse mouth well with water. Drink large glass of water. Seek medical attention.

5. Fire-fighting Measures

Flash Point (Method Used): None to boiling

Extinguishing Media: Use normal firefighting procedures and media appropriate for surrounding materials

Special Firefighting Procedures: None

Unusual Fire and Explosion Hazards: None

6. Accidental Release Measures

Steps to be taken in Case Material is Released or Spilled: Absorb spilled liquid into absorbent media.

Waste Disposal Method: Any method in accordance with local, state and federal laws.

7. Handling and Storage

Keep out of reach of children.Store in original shipping containers, under cover and in ambient temperatures, not exceeding 113F. Do not store in direct heat or sunlight. Avoid storage in freezing temperatures. Keep closed when not in use. Do not store in direct heat or sunlight. Keep closed when not in use.

8. Exposure controls and personal protection

Respiratory Protection: No special requirements. Ventilation Requirements: Normal indoor ventilation is adequate. Protective

Gloves: Recommended for prolonged or repeated contact. Eye Protection: None required due to nature of product application.

Other Protective Equipment: None needed. Hygenic Work Practices: Rinse hands after handling.

9. Physical and chemical properties

Boiling Point (°F):	>212 F.
Specific Gravity:	1g/ml
Vapor Pressure:	PSIG @70oC
Vapor Density (Air=1):	N/A
pH:	9.0-10.0
Solubility in Water:	Total
Evaporation Rate (Water=1):	ND
Water Reactive:	No
Physical Description:	White, nonwoven media with large “weave pattern embossed texture”, synthetic blend wipes moistened with clear, colorless liquid with pleasant odor.

10. Stability and reactivity

Stability: Stable
Hazards Decomposition Products: Oxides of carbon, Nitrogen and Sulfer

Hazardous Polymerization: Will not occur.

Incompatibility (Materials to Avoid): Strong oxidizers

11. Toxicological information

12. Ecological information

13. Disposal considerations

14. Transport information

15. Regulatory information

SARA Title III - Section 311/312 -Hazard Categories:
No - Fire Hazard
No - Sudden Release of Pressure Hazard
No - Reactivity Hazard
No - Immediate (acute) Health Hazard
NE - Delayed (chronic) Health Hazard

16. Other information