Material Safety Data Sheet

SODIUM SELENATE AR ANHYDROUS (RXSOL-60-6605-565)

1. Product and Company Identifaction

Product Name	RXSOL-60-6605-565
Product Type	SODIUM SELENATE AR ANHYDROUS
Revised date	

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Chennai, Visakhapatnam, Kolkata, Fujairah, Muscat Barka

Phone	+91 22 27815541 / 42
Fax	+91 22 2781 1318 :::AOH :0091 9821214367
Email	mail@rxmarine.com

2. Composition / informationon ingredients

Substance / Preparation : SODIUM SELENATE AR ANHYDROUS
CAS No :13410-01-0
Substance.
Contains no other components or impurities which will influence the classification of the product.

3. Hazards Identification

3.1. Classification of the substance or mixture
Classification EC 67/548 or EC 1999/45
Classification : T; R23/25 R33 N; R50-53
Hazard Class and Category Code(s), Regulation (EC) No 1272/2008
(CLP) Health hazards : Acute toxicity, Inhalation - Category 3 - Danger (CLP : Acute Tox. 3) H331
Acute toxicity, Oral - Category 3 - Danger (CLP : Acute Tox. 3) H301
Environmental hazards : Hazardous to the aquatic
environment - Acute hazard - Category 1 - Warning (CLP : Aquatic Acute 1) H400
Hazardous to the aquatic environment - Chronic hazard - Category 1 - Warning (CLP : Aquatic Chronic 1) H410
3.2. Label elements
Labelling EC 67/548 or EC 1999/45
Symbol(s) : T : Toxic
N : Dangerous for the environment
R Phrase(s) : R23/25 : Toxic by inhalation and if swallowed.
R33 : Danger of cumulative effects.
R50/53 : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S Phrase(s) : S20/21 : When using, do not eat, drink or smoke.
S28 : After contact with skin, wash immediately with
S45 : In case of accident or if you feel unwell, seek medical advice immediately (show the label when possible).
S60 : This material and its container must be disposed of as hazardous waste.
S61 : Avoid release to the environment. Refer to special instructions/Safety data sheets.
Labelling Regulation EC 1272/2008 (CLP)

Signal words : Danger

Hazard statements : H301 : Toxic if swallowed.
H331 : Toxic if inhaled.
H410 : Very toxic to aquatic life with long lasting effects. Precautionary statements
• Prevention : P271: Use only outdoors or in a well-ventilated area.
P261: Avoid breathing dust, fume, gas, mist, vapours, spray.
P273: Avoid release to the environment.
P264: Wash thoroughly after handling.
P270: Do not eat, drink or smoke when u