Material Safety Data Sheet

STANNOUS CHLORIDE AR (RXSOL-60-6605-604)

1. Product and Company Identifaction

Product Name	STANNOUS CHLORIDE AR
Part Number	RXSOL-60-6605-604

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone	+91 22 20871200 - 1400
Fax	+91 22 27612100 :::AOH :0091 9821214367
Email	mail@rxmarine.com
Website	www.rxmraine.com

2. Composition / informationon ingredients

Chemical Name	CAS	EC number	Weight	Formula
Stannous chloride	7772-99-8	231-868-0	= 100 %	Cl_2Sn

3. Hazards Identification

Signal Word	Danger
Hazard Statements	H290 May be corrosive to metals. H302 + H332 Harmful if swallowed or if inhaled. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H373 May cause damage to organs (Cardio-vascular system) through prolonged or repeated exposure if swallowed. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	P260 Do not breathe dust. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Classification of the substance or mixture	Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.
Supplemental Hazard Statements	None.
Other hazards	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

4. First Aid Measures

General advice	First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.
If inhaled	After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.
Eye Contact	After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

Swallowed	After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.
Skin Contact	In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.
Inhalation	Remove patient to fresh air, keep warm and at rest and get medical assistance in necessary.
Ingestion	Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.
Most important symptoms and effects, both acute and delaye	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Indication of any immediate medical attention and special treatment needed	No data available

5. Fire-fighting Measures

Flammability	May be combustible at high temperature.
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	For this substance/mixture no limitations of extinguishing agents are given.
Special hazards arising from the substance or mixture	Hydrogen chloride gas Tin/tin oxides Not combustible. Ambient fire may liberate hazardous vapours.
Further information	Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Hazardous combustion products	Fire may cause the evolution of Sulphur oxides, nitrogen oxides.
Advice for firefighters	Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.
Protective Equipment	Use personal protective equipment.
Specific Hazards Arising from the Chemical	Has a fire-promoting effect due to the release of oxygen. Ambient fire may liberate hazardous vapours.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
Spillage	Oxidizing material. Stop leak if without risk. Avoid contact with a combustible material (wood, paper, oil, clothing...). Keep substance damp using water spray. Do not touch spilled material. Prevent entry into sewers, basements or confined areas dike if needed. Eliminate all ignition sources. Call for assistance on disposal.
Personal Protection	Advice for non-emergency personnel: Avoid inhalation of dusts. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Protective equipment see section 8.
Enviromental Precaution	Do not let product enter drains.
Methods and materials for containment and cleaning	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

7. Handling and Storage

Advice on protection against fire and explosion	Work under hood. Do not inhale substance/mixture.
Incompatible materials	Keep away from alkalis, strong oxidizing agents and metals. Provide containment walls of adequate capacity to hold any accidental spills.
Hygiene measures	Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.
Precautions for safe handling	Provide appropriate exhaust ventilation at places where dust is formed.
Conditions for safe storage, including any incompatibilities	Store the container tightly closed in a dry, cool and well-ventilated place. Store apart from foodstuff containers or incompatible materials.
Storage conditions	No metal containers. Tightly closed. Dry. Moisture sensitive. Store under inert gas.
Storage class	Storage class (TRGS 510): 8B: Non-combustible, corrosive hazardous materials
Specific end use(s)	Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

Advice on general occupational hygiene	Advice on safe handling Observe label precautions. Change contaminated clothing. Wash hands after working with substance.
Requirements for storage	Keep in cool and store under shade.

8. Exposure controls and personal protection

Exposure controls	No specific additional engineering controls are required. Provide good natural or artificial ventilation.
Engineering Control	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.
Eye/face protection	Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles
Body Protection	Acid-resistant protective clothing
Skin protection	This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: Nitrile rubber Minimum layer thickness: 0,11 mm Break through time: 480 min Material tested:KCL 741 Dermatril® L This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: Nitrile rubber Minimum layer thickness: 0,11 mm Break through time: 480 min Material tested:KCL 741 Dermatril® L
Respiratory protection	Recommended Filter type: Filter B-(P2) The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.
Other Protection Measure	Handle in accordance with good industrial hygiene and safety practice.
Control of environmental exposure	Do not let product enter drains.

9. Physical and chemical properties

Physical state	Powder
Colour	White
Odour	Odorless
Odor Threshold	Not Applicable
pH	2,18 at 20 °C
Melting Point	246 °C - lit.
Boiling Point	652 °C - lit.
Flash Point	No data available
Evaporation Rate	Not Applicable
Flammability (solid, gas)	No data available
Explosive limits	No Data Available
Upper/lower flammability or explosive limits	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Viscosity,kinematic	No data available
Vapour pressure	33 hPa at ca.429 °C
Density	ca.3,9 g/cm3 at 20 °C
Relative Vapour Density	No data available
Freezing point	No data available
Specific Gravity	No data available
Partition coefficient	No data available
Explosive properties	No data available

Solubility	ca.178 g/l at 20 °C
Ignition temperature	No information available.
Particle characteristics	No data available

10. Stability and reactivity

Reactivity	No data available
Stability	The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	Violent reactions possible with: Strong acids hydrogen peroxide Risk of ignition or formation of inflammable gases or vapours with: halogen-halogen compounds carbides Risk of explosion with: hydrazine and derivatives nitrates Alkali metals Strong oxidizing agents
Conditions to avoid	Avoid moisture. no information available
Incompatible materials	No data available
Hazardous Polymerization	In the event of fire: see section 5

11. Toxicological information

Acute toxicity	LD50 Oral - Rat - male - 1.910 mg/kg (OECD Test Guideline 423) Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach. Acute toxicity estimate Oral - 1.910 mg/kg (ATE value derived from LD50/LC50 value) LC50 Inhalation - Rat - male and female - 4 h - 2 mg/l - dust/mist (OECD Test Guideline 436) Remarks: Calculation method Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract Acute toxicity estimate Inhalation - 2 mg/l - dust/mist (ATE value derived from LD50/LC50 value) Dermal: No data available
Skin corrosion/irritation	Skin - Rabbit Result: Corrosive - 4 h (OECD Test Guideline 404)
Serious eye damage/eye irritation	Remarks: Causes serious eye damage.
Respiratory or skin sensitization	Patch test: - Human Result: positive Remarks: (ECHA)
Carcinogenicity	No data available
Germ cell mutagenicity	Test Type: In vitro mammalian cell gene mutation test Test system: Mouse lymphoma test Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative Test Type: Mutagenicity (mammal cell test): micronucleus. Species: Mouse Application Route: Intraperitoneal injection Result: negative Remarks: (National Toxicology Program)
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	May cause respiratory irritation.
Special Remarks on other Toxi Effects on Humans	Acute Potential Health Effects: Skin: Causes skin irritation. May cause skin sensitization, an allergic reation, which becomes evident upon re-exposure to this material. Eyes: Causes eye irritation. Ingestion: Causes gastrointestinal (digestive) tract irritation with nausea, vomiting, and diarrhea. May be harmful if swallowed. Inhalation: Causes respiratory tract irritation. May cause chemical pneumonitis and pulmonary edema, inflammation, edema of bronchi and larynx. Chronic Potential Health Effects: Repeated or prolonged skin exposure may cause allergic reactions in sensitive individuals. Repeated or prolonged exposure by inhalation may affect respiration and metabolism.
Additional Information	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. RTECS: XP8700000 Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Systemic effects: Metal-fume fever after inhalation of large quantities. Other dangerous properties can not be excluded. Handle in accordance with good industrial hygiene and safety practice.

12. Ecological information

Persistence and degradability	The methods for determining the biological degradability are not applicable to inorganic substances.
Bioaccumulative potential	No data available
Toxicity to fish	Static test LC50 - other fish - 10,19 mg/l - 96 h Remarks: (ECHA)

Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia - 22 - 55 mg/l - 48 h Remarks: (ECHA)
Toxicity to algae	Static test ErC50 - Pseudokirchneriella subcapitata (green algae) - > 17,7 mg/l - 72 h (OECD Test Guideline 201) Remarks: The value is given in analogy to the following substances: Sodium tungstate static test EC10 - Pseudokirchneriella subcapitata (green algae) - 5,76 mg/l - 72 h (OECD Test Guideline 201) Remarks: The value is given in analogy to the following substances: Sodium tungstate
Toxicity to bacteria	Static test - activated sludge - > 1.000 mg/l - 30 min (OECD Test Guideline 209)
Mobility in soil	No Information available
Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Endocrine disrupting properties	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Other adverse effects	Biological effects: Harmful effect due to pH shift. Discharge into the environment must be avoided.

13. Disposal considerations

Disposal methods	The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.
Contaminated packaging	Dispose of as unused product.
Waste treatment Method	No data available

14. Transport information

UN number	ADR/RID: 3260	IMDG: 3260	IATA: 3260
UN proper shipping name	ADR/RID:Corrosive solid, acidic, inorganic, n.o.s. (tin(II) chloride)		
	IMDG:Corrosive solid, acidic, inorganic, n.o.s. (tin(II) chloride)		
	IATA:Corrosive solid, acidic, inorganic, n.o.s. (tin(II) chloride)		
Transport hazard class(es)	ADR/RID: 8	IMDG: 8	IATA: 8
Packaging group	ADR/RID: II	IMDG: II	IATA: II
Environmental hazards	ADR/RID: No	IMDG: No	IATA: No
Special precautions for user	Tunnel restriction code : (C/E)		
Further information	Not classified as dangerous in the meaning of transport regulations.		
Transport in bulk according to IMOinstruments	No data available		

15. Regulatory information

Inventory status	Components are on the following inventories: Polymaleic acid: - US TSCA, Canadian DSL, EU EINECS, Australian AICS, Korean, Philippine PICCS and Chinese Xi irritant R 36/38 Irritant to eyes & skin R 41 Risk of serious damage to eyes S24/25 Avoid contact with skin and eyes S26/28 In case of contact eyes & skin, rinse with plenty water and seek medical advice Section 312/313: Not listed. Not listed under California proposition 65.
Safety, health and environmental regulations/legislation specific for the substance or mixture	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
National legislation	Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E1 ENVIRONMENTAL HAZARDS
Other regulations	Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.
Chemical Safety Assessment	For this product a chemical safety assessment was not carried out

16. Other information

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and weassume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages.